


# Product 41

## Series 4A Set Up:


### Step 1- Adjust the shoulder width adjustment

You will want to measure the width of your neck (diag. 1-A). The Series 4A has a neck width that ranges from 4.75 to 7.75 inches. Upon establishing that measurement, you will want to adjust your shoulder adjustment (diag. 1-B) to 1 inch wider than your neck measurement. Remove 4 screws and binary posts and set to correct position. If you will be adjusting wider than the setting out of the box, you may need to loosen the strap, video instructions



### Step 2- Adjust the UPPER ARM Angle


It is recommended that you adjust this in your race seat to get the best angle for your individual needs. There are two screws on each side (diag. 2-A ). Screw #1 is the only screw that needs to be removed to adjust angle. Screw #2 does not need to be removed and it has thread lock on it from mfg. Remove Screw #1, and adjust the arm angle so that fits snug against body, but does not protrude into your body. Adjust both sides to same angle.



**Upon completion of steps 1-2**, once you are 100% happy with the fit of your restraint, we recommend that at this time you remove all screws one at a time (except screw #2 in step 2) and secure them with tread lock “blue” and tighten snug.

### Step 3- Adjust tethers and strapping

It is recommended that you evaluate the video [here](#) in regards to adjustment of tethers and strapping. You will want to make sure the strapping stays in the same configuration throughout the hardware as you receive it from the mfg. There are two points which you will want to adjust (diag. 4-A). Point #1 should be adjusted to 2.75 inches (70mm) and Point #2 should be adjusted to approx. 1.75 inches (45mm).



### Step 4- Setting Up Helmet

Installation of Z-Tech hardware will depend on if your helmet has a certified M6 Insert or a Predrilled. Helmet inserts that are not certified are not recommended.

**M6 Inserts**– Set Part #2 against helmet shell centered to the insert. Then put the M6 Screw provided through Part #1 with thread lock “blue” on the end of the screw. Align Part #1 and M6 Screw through Part #2 and carefully screw the M6 insert into the helmet without cross threading during installation. Tighten snugly and allow thread lock to dry.

**Predrilled**– You will first need to install Z-Tech nut washer Part #3 on the interior of the shell. Slide Part #3 between the Shell and EPS/Dense foam upper liner, carefully positioning it center to the predrilled hole. Once Part #3 is positioned correctly, then you can move on. Set Part #2 against helmet shell centered to the insert. Then put the M6 Screw provided through Part #1 with thread lock “blue” on the end of the screw. Align Part #1 and M6 Screw through Part #2 and carefully screw the M6 insert into the helmet without cross threading during installation. Tighten snugly and allow thread lock to dry.

